



tira led 5050

ficha técnica

datasheet



ref. 5551047



| | |
|--|------------------------------------|
| Nombre / Name | tira led 5050 • C+N+F |
| Referencia / Reference | 5551047 |
| Materiales / Materials | Cobre + Plástico / Coper + Plastic |
| LED / mt | 60led/mt |
| Potencia / Power | 6W/mt |
| Temperatura de color / Color temperature | Dualcolor |
| Flujo luminoso / Luminoux flux | 575lm/mt |
| Dimable / Dimmable | Opcional / Optional |
| Ángulo de apertura / Beam angle | 120° |
| Ángulo de inclinación / Inclination angle | - |
| IP | 65 |
| IK | - |
| F.P | - |
| UGR | - |
| IRC | >80 |
| Chip | EPISTAR SMD 5050 |
| Driver | - |
| Vida media (duración) / Average life | ± 40,000h |
| Clase energética / Energy class | A+ |
| Aislamiento eléctrico / Electrical isolation | - |
| Colores / Colors | Transparente / Transparent |
| Medida exterior / Product size | 5mts x 10mm |
| Medidas de corte / Cutting measurements | Cada 100mm / every 100mm |
| Tª (ambiente/trabajo) / Tª (enviroment/work) | -20°C ~ 45°C |
| Input | - |
| Output | DC24V |
| Frecuencia / Frequency | 50/60Hz |
| Peso / Weight | 238grs rollo / 238grs roll |
| Certificados / Certificates | CE RoHS |
| Garantia / Warranty | 2 años / 2 years |